



BUSHING SPECIFICATIONS							
PART#	D1-diameter 1	D2- diameter 2	F- flange	L-length	TOLERANCE +/-	THREAD	QUANTITY

Please fill out the table above according to your specs.

**\*The screws and bushings are also available as matched sets\***

Note: Screws and bushings with threads from 170TPI up to .1mm are sold by sets only.

**Notes:**

- Threads available:  
80TPI, 100TPI, 127TPI,  
170TPI,200TPI, .2mm,.1mm
- Max bushing length for screws 5"  
and above is 1"
- Max ID .750"

**MATERIAL:**

- HALF HARD BRASS
- PHOSPHOR BRONZE
- 510 ALLOY-(ASTM B139)

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <INSERT COMPANY NAME HERE>. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <INSERT COMPANY NAME HERE> IS PROHIBITED.

		DIMENSIONS ARE IN INCHES		NAME	DATE	<b>BUSHING</b>	
		TOLERANCES:		Juan P	9/12/09		
		FRACTIONAL ±		CHECKED		<b>KOZAK PRECISION PRODUCTS</b> 193 Franklin Rd Randolph, NJ 07869 Phone# 973-442-9100 Fax# 973-442-1448	
		ANGULAR: MACH ± BEND ±		ENG APPR.			
		TWO PLACE DECIMAL ±		MFG APPR.			
		THREE PLACE DECIMAL ±		Q.A.			
		MATERIAL		COMMENTS:		SIZE <b>A</b> DWG. NO. _____ REV. _____	
NEXT ASSY	USED ON	FINISH --				SCALE:1:1 WEIGHT: _____ SHEET 1 OF 1	
APPLICATION		DO NOT SCALE DRAWING					